

## Datasheet for Top cloth: 20-10.201

### Features

With decades of filtration experience Filtration Group B.V. has developed a cloth range to give a solution to all your filtration challenges.

Our broad range of top cloths is developed in such a way that depending on the demanded temperature range, chemical resistance and selectivity the best solution for your process can be chosen.

### Characteristics

- High strength seams - no breaks. This brings stand-down time to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It saves time when installing a cloth.
- Packed in plastic bags to prevent the cloths from becoming dirty.
- A sticker on the plastic bag identifies the cloths. Because the identification sticker does not touch the cloth itself there is no risk of ink or glue going into hygienic applications.

### Specifications

Cloth code	20-10.201
Cloth use	Top cloth
Material	PETP
Cloth structure	Monofilament
Surface treatment	Heat-set and calendered
Filter fineness [µm]	-
Air permeability [l/dm <sup>2</sup> /min] at 200 Pa	230 ± 15%
Maximum temperature [°C]	150

### Approvals

Not approved according to 2004/1935/EG or the FDA.

### Recommendations

Use in combination with drain cloth 20-00.001 to further improve the filtration flux and the lifetime of the top cloth (Cricket filter only).

Filtration Group B.V.  
Postbus 35  
7240 AA Lochem  
The Netherlands

+31 (0) 57-329 77 77

info.fgnl@filtrationgroup.com  
www.filtration.group

October, 2017

**Order Information**

<b>Element type</b>	<b>Length</b>	<b>Ordering Code</b>
Type I	620	-
	750	-
	1000	72432863
	1500	72432864
	2000	-
Type II	1000	-
	1500	72432865
	2000	-
	2500	-
PTS 70 mm	1500	-
	1750	-
	2000	-
PTS 90 mm	1000	72381056
	1500	-
	1750	-
	2000	-
	2250	-
	2500	-

Filtration Group B.V.  
Postbus 35  
7240 AA Lochem  
The Netherlands

+31 (0) 57-329 77 77

info.fgnl@filtrationgroup.com  
www.filtration.group

October, 2017