

Datasheet for Top cloth: 45-20.101

Features

With decades of filtration experience Filtration Group B.V. has developed a cloth range to give a solution to all your filtration challenges.

Our broad range of top cloths is developed in such a way that depending on the demanded temperature range, chemical resistance and selectivity the best solution for your process can be chosen.

Characteristics

- High strength seams - no breaks. This brings stand-down time to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It saves time when installing a cloth.
- Packed in plastic bags to prevent the cloths from becoming dirty.
- A sticker on the plastic bag identifies the cloths. Because the identification sticker does not touch the cloth itself there is no risk of ink or glue going into hygienic applications.

Specifications

Cloth code	45-20.101
Cloth use	Top cloth
Material	PVDF
Cloth structure	Multifilament
Surface treatment	Untreated
Filter fineness [µm]	-
Air permeability [l/dm ² /min] at 200 Pa	7
Maximum temperature [°C]	110

Filtration Group B.V.
Postbus 35
7240 AA Lochem
The Netherlands

+31 (0) 57-329 77 77

info.fgnl@filtrationgroup.com
www.filtration.group

October, 2017

Approvals

Not approved according to 2004/1935/EG or the FDA.

Order Information

Element type	Length	Ordering Code
PTS 70 mm	1500	-
	1750	-
	2000	-
PTS 90 mm	1500	-
	1750	-
	2000	-
	2250	70483757
	2500	-

Filtration Group B.V.
Postbus 35
7240 AA Lochem
The Netherlands

+31 (0) 57-329 77 77

info.fgnl@filtrationgroup.com
www.filtration.group

October, 2017