

## Datasheet for Top cloth: 50-20.201

### Features

With decades of filtration experience Filtration Group B.V. has developed a cloth range to give a solution to all your filtration challenges.

Our broad range of top cloths is developed in such a way that depending on the demanded temperature range, chemical resistance and selectivity the best solution for your process can be chosen.

### Characteristics

- High strength seams - no breaks. This brings stand-down time to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It saves time when installing a cloth.
- Packed in plastic bags to prevent the cloths from becoming dirty.
- A sticker on the plastic bag identifies the cloths. Because the identification sticker does not touch the cloth itself there is no risk of ink or glue going into hygienic applications.

### Specifications

Cloth code	50-20.201
Cloth use	Top cloth
Material	PPS
Cloth structure	Multifilament
Surface treatment	Calendered
Filter fineness [ $\mu\text{m}$ ]	5
Air permeability [ $\text{l}/\text{dm}^2/\text{min}$ ] at 200 Pa	5
Maximum temperature [ $^{\circ}\text{C}$ ]	190

### Approvals

Approved according to FDA, declaration of conformity available on request.



**Wash the filter cloth before use.**

Filtration Group B.V.  
Postbus 35  
7240 AA Lochem  
The Netherlands

+31 (0) 57-329 77 77

info.fgnl@filtrationgroup.com  
www.filtration.group

## Order Information

Element type	Length	Ordering Code
PTS 70 mm	1500	72422618
	1750	-
	2000	-
PTS 90 mm	1500	-
	1750	-
	2000	-
	2250	-
	2500	-

Filtration Group B.V.  
Postbus 35  
7240 AA Lochem  
The Netherlands

+31 (0) 57-329 77 77

[info.fgnl@filtrationgroup.com](mailto:info.fgnl@filtrationgroup.com)  
[www.filtration.group](http://www.filtration.group)

October, 2017